







#### American Association of State Highway and Transportation Officials

#### Seven (7) Page Form

An Application from the State Highway or Transportation Department of Kentucky

for (sel	ect one of the following):					210 X 5001	
x	Elimination of a U.S. (Interstate) Route Establishment of a U.S. (Interstate) Route Extension of a U.S. (Interstate) Route Relocation of a U.S. (Interstate) Route US 119 Establishment of a U.S. Alternate Route Establishment of a Temporary U.S. Route **Recognition of a Business Route on U.S. (Interstate) Route  **Recognition of a By-Pass Route on U.S. Route  *Establishment of a U.S. Bicycle Route (A NEW FORM IS BEING  DEVELOPED FOR US BIKE ROUTES – continue to use this until the new form is finalized) *Relocation of a U.S. Bicycle Route (SAA)			numbering tee on Highways			
	Between Open Fork and Pikeville  The following states or states are involved:  Kentucky	<b>X</b>		g Committee o	n Highways		
•	* Bicycle Routes: Attach map on page 3. Obtain Signatures, page 4.  Type a statement indicating that there are no deficiencies on the proposed US Bike Route. Other sections not applicable.	For AASHTO Use Only	600 1100	Date considered by the Standing Committee on Highways	Action of Standing Committee on Highways		Member Department Notified

- \*\*"Recognition of..."A local vicinity map needed on page 3. On page 6 a short statement to the effect that there are no deficiencies on proposed routing, if true, will suffice.
- If there are deficiencies, they should be indicated in accordance with page 5 instructions.
- All applications requesting Interstate establishment or changes are subject to concurrence and approval by the FHWA

DATE SUBMITTED Select from Calendar: August 29, 2008

SUBMIT APPLICATION ELECTRONICALLY TO usroutes@aashto.org

You may convert your form as a PDF file, print then scan or submit as a saved word file. Send only one copy, please.

The purpose of the **United States** (U.S.) **Numbered Highway System** is to facilitate travel on the main interstate highways, over the shortest routes and the best available roads. A route should form continuity of available facilities through two or more states that accommodate the most important and heaviest motor traffic flow in the area.

The routes comprising the **National System of Interstate and Defense Highways** will be marked with its own distinctive route marker shield and will have a numbering system that is separate and apart from the U.S. Numbered Highway System. For the convenience of the motorist, there must be continuity and a uniform pattern of marking and numbering these Interstate routes without regard to state lines.

The U.S. Numbered System was established in 1926 and the Interstate Numbered System was established in 1956. Both have reached the period of review, revision, and consolidation. They now need perfecting rather than expansion. Therefore, any proposed alteration in the established systems should be extremely meritorious and thoroughly, though concisely, explained in order that the Special Committee on U.S. Route Numbering and the Standing Committee on Highways of the Association may give prompt and proper consideration to each and every request made by a member department.

Explanation and Reasons for the Request (US and Interstates Only): (Keep concise and pertinent.)


This section of new US 119 was built to continue to provide a safer, shorter, and more efficient route to interstate traffic. It has been drastically straightened, removing potentially dangerous curves and intersections. Much of US 119 through Pike County has already been improved as part of the Appalachian Development Highway System (ADHS). This is the last section of US 119 in Pike County to be improved with ADHS funds.

The Cabinet proposes to route U.S. 119 onto the newly constructed roadbed north of Pikeville in Pike County, Kentucky. This new route should particularly facilitate travel between Pikeville, the Eastern Kentucky region, and West Virginia.

Date facility available to traffic? March 2008

Does the petition propose a new routing over a portion of an existing U.S. Route? <u>No</u> If so, where?

Does the petition propose a new routing over a portion of an existing Interstate Route? <u>No</u> If so, where?



# US 119 / KY 1426 Pike County, Kentucky Proposed Routing Other State Primary Road System Other State Primary State Secondary Rural Secondary Supplemental Road Pikeville

The State agrees and pledges its good faith that it will not erect, remove, or change any U.S. or Interstate Route Markers on any road without the authorization, consent, or approval of the Standing Committee on Highways of the American Association of State Highway and Transportation Officials, not withstanding the fact that the changes proposed are entirely within this State.

The weighted average daily traffic volume along the proposed route, as shown on the map on page 3, is  $\underline{12,195}$  as compared to  $\underline{8,390}$  for the year  $\underline{2007}$  for all other U.S. Numbered Routes in the State.

**Chief Executive Officer** 

The Purpose and Policy in the Establishment and Development of the United States Numbered Highways, as Retained from October 3, 1991 or the Purpose and Policy in the Establishment of a Marking System of the Routes Comprising the National System of Interstate and Defense Highways as Retained from August 10, 1973 has been read and is accepted.

In our opinion, this petition complies with the above applicable policy.

(Signature Required – see note below)

Secretary

Kentucky Transportation Cabinet (Member Department)

This petition is authorized by official action of

under date of

as follows: (Copy excerpt from minutes.)

#### (This includes US, Interstates and Bicycle Routes)

A **letter** from your Chief Executive Officer with the **CEO's signature** is sufficient when submitting your application, if you choose not to include the signature on this form.

#### (US and Interstates Only)

#### Instructions for Preparation of Page 6

**Column 1:** Control Points and Mileage. Top of column is one terminus of road. Indicate control points by identical number as shown on map on page 3. Show mileage between control points in miles and tenths.

Column 2: Pavement Type. Code
High type, heavy duty
Intermediate type
I ow type dustless

Low type, dustless L (show in red)
Not paved N (show in red)

Column 3: Pavement Condition Code

Excellent E

Good G

Fair F (show in red)
Poor P (show in red)

NOTE: In columns 2 and 3, where pavements types and conditions change, the location of the change shall be indicated by a short horizontal line at the proper place opposite the mileage log and the proper code letter (shown above) shall be entered in the respective column between the locations so indicated.

Column 4: Traffic. Indicate average daily traffic volumes in this column. Points of changes in these data to be indicated by short horizontal lines opposite the appropriate mileage point on the mileage log. Any existing main line rail crossing that is not separated shall be indicated at the appropriate

mileage point by RXR - black if signalized - red if not protected by signals.

Columns 5 & 6 Pavement Width and Shoulder Width. These columns to be completed by comparing standards

of highway involved with applicable AASHTO standards. Entries that fall to the right of the tolerance lines (dashed) should be shaded in red. If there are no deficiencies indicate by use of

the word NONE.

**Columns 7 & 8**Major Structures. Show in these columns those structures that do not meet AASHTO standards.

Show by horizontal line sufficiently long to indicate percentage of deficiency. Portion on right of tolerance line shall be shown in red. Indicate length of structure in feet immediately under the line. Any sub-standard highway underpass structure shall be shown opposite the appropriate mileage point by the designation LP with the vertical clearance in feet following and shown in red. If there

are no deficiencies indicate by the use of the word NONE.

**Column 9:** Vertical Sight Distance. Items to be shown in this column as a horizontal line, the length of

which will indicate the deficiency as determined in accordance with comparisons with comparable

AASHTO standards. Portions of the line past the tolerance line shall be shown in red.

**Column 10:** Horizontal Curvature. Curves in excess of AASHTO applicable standards to be shown in this

column by a short horizontal line with degree of curve shown immediately above the line. To be

shown in red.

Column 11 Percent Grades. Show by horizontal lines opposite proper mileage point on mileage log. Show

percent of grade above the line and length of grade in feet immediately below. To be shown in

red.

What follows is an Excel worksheet that you can open by right clicking your mouse and select "Worksheet Object" – you can then Edit, Open or Convert but you must first unlock the form as show when inserting maps.

#### AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS

ſ	1	2	3 Z	4	5	6 COMPARISON	TO APPLICABLE	8 E AASHTO DESIG	9 N STANDARDS	10	11
MILEAGE	CONTROL POINTS AND MILEAGE	IYPE	PAVEMENT CONDITION	TRAFFIC ADT	PAVEMENT WIDTH DEFICIENCY	SHOULDER WIDTH DEFICIENCY	MAJOR STRUCTURES		T	SHOW WHEN IN EXCESS	
		PAVEMENT TYPE					ROADWAY WIDTH DEFICIENCY	H - LOADING DEFICIENCY	SIGHT DISTANCE DEFICIENCY	HORI- ZONTAL CURVA- TURE	PERCENT GRADE
0	CON	۵	PAV		PERCENT 10 20 30 40	PERCENT 20 40 60 80	PERCENT 10 20 30 40	PERCENT 20 40 60 80	PERCENT 20 40 60 80		LENGTH
40	1) 15 2) 23	н	E E	9,140 13,100	10 20 30 40 20 40 60 80 10 20 30 40 20 40 60 80 20 40 60 80   DEGREE   LENGTH						
		il.									
30											
									-		
0											
	360										
60											
									ı		
	_									(4)	
	×				=						L
60								=			

### (This includes US, Interstates and **Bicycle Routes**) Contact regarding this application:

Name: Dawn Mattingly

Address: Kentucky Transportation Cabinet, Division of Planning, 200 Mero Street, 5th floor West, Frankfort, KY 40601

Telephone Number: 502-564-7183

Fax Number: 502-564-2865

Email Address: dawn.mattingly@ky.gov

**Description** to be provided to the AASHTO Highways Special Committee on US Route Number (USRN) when they review this application:

- o Where does the route begin? (Intersection or Mile Marker) It begins on existing US 119 northeast of Pikeville near the intersection with KY 881.
- o Describe where it is going? It will travel southwest to another point on existing US 119 near the intersection with KY 1426.
- What type of facility is it traveling over? (New alignment or over an existing pathway) It is traveling over new alignment.
- Give the direction of travel(north, east, south, and west) Southwest
- Name the focal point city or cities North of Pikeville near Meta and Zebulon
- Length of route in miles. The new US 119 segment is approximately 7.686 miles long.
- Where does it end? (Terminal intersection or mile marker) It ends on existing US 119 near the intersection with KY 1426

#### KENTUCKY TRANSPORTATION CABINET

## U.S. Numbered Route Mileage For Submission To AASHTO U.S. 119 -- Kentucky

State	Type	Intersection	Point to Point Mileage	Accumulated Mileage in State	Remarks
Kentucky	Regular	West Virginia State Line	0	0	
		Jct N Pikeville	26	26	Joins US 23, US 460
		Jct S Pikeville/Shelbiana	7	33	Leaves US 460
		Jct S Jenkins	25	58	Leaves US 23
		Harlan	53	111	Joins US 421
		Harlan	1	112	Leaves US 421
		Pineville	29	141	Route ends, junction US 25E